PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

WO 97/30212 (51) International Patent Classification 6: (11) International Publication Number: A1 D21F 1/48, 1/38 (43) International Publication Date: 21 August 1997 (21.08.97) (81) Designated States: BR, CA, GB, HU, JP, NO, US, European PCT/GB97/00425 (21) International Application Number: patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). 14 February 1997 (14.02.97) (22) International Filing Date: **Published** (30) Priority Data: With international search report. GB 14 February 1996 (14.02.96) 9602984.8

(71) Applicant (for all designated States except US): PLASMA COATINGS LIMITED [GB/GB]; Industrial Estate, Tideswell, North Derbyshire SK17 8PY (GB).

(72) Inventor; and


(75) Inventor/Applicant (for US only): ANDERSON, Duncan [GB/GB]; Winthorpe House, Broad Elms Lane, Whirlow, Sheffield, Yorkshire S11 9RQ (GB).

(74) Agent: SUER, Steven; Ablett & Stebbing, 45 Lancaster Mews, Lancaster Gate, London W2 3QQ (GB).

(54) Title: FOIL BLADE

(57) Abstract

The present invention concerns a foil blade (1) and its method of manufacture. The blade comprises a substrate (3) and a wear-resistant layer (2), the wear-resistant layer being applied as an adhesive, the adhesive comprising wear-resistant particles suspended in an unset settable material.



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	. IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PŁ	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania .
BY	Belanis ·	KG	· Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CIF	Central African Republic		of Korea	SE	Sweden
CG.	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ.	Kazakhstan	SI	Slovenia
<u> </u>	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
cz	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
RE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
⇔ Fi	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	· VN	Vict Nam

FOIL BLADE

The present invention relates to a blade for use in apparatus such as that used for forming and processing material in sheet form, and particularly to a wear-resistant foil blade suitable for conveying a moving paper web during the manufacture of paper.

Blade arrangements in existence incorporate the use of coatings that are thermally sprayed onto metal blades. Such blades can subsequently be bonded or held in close contact with a plastic sub-structure.

Thermal spraying techniques have a disadvantage in that they are expensive, requiring costly spraying equipment and associated safety equipment and also involve a high energy consumption. Furthermore, thermal spraying techniques present difficulties in depositing a wear-resistant layer directly onto a plastics sub-structure in view of the high temperatures that can damage the sub-structure. This is disadvantageous in view of the cost and weight advantages that plastics can afford over metal.

It is therefore an object of the present invention to provide 25 a blade and a method of manufacture thereof which overcomes the disadvantages of the prior art.

According to an aspect of the present invention there is provided a method of manufacture of a blade comprising a substrate and a wear-resistant layer, the method including the step of:-

applying the wear-resistant layer in the form of an adhesive, the adhesive comprising wear-resistant particles suspended in an unset settable material.

Preferably, the adhesive is sprayed onto the blade substrate. Spraying is advantageous in that it provides an even

35

- 2 -

distribution of material onto the blade substrate. Alternatively however, the adhesive may be applied mechanically to the blade substrate, for example by extrusion techniques.

5

Conveniently, the method comprises the further step of adding further blade surface materials whilst the adhesive is unset. Such further materials may be applied by thermal spraying or by mechanical means.

10

The method may comprise the step of applying pre-formed wearresistant tiles onto the blade substrate and applying the adhesive between edges of adjacent tiles.

15 The present invention further encompasses a blade manufactured according to the materials defined above.

In preferred embodiments, the adhesive comprises a polymer material in which is suspended any of silicon carbide, tungsten, alumina, zirconia or chrome oxide particles.

Preferably the blade substrate is recessed in an area where the adhesive is to be applied. Such recessing facilitates the application of the adhesive layer.

25

20

Conveniently, the substrate comprises a removable member onto which the wear-resistant layer is formed. The removable member may be hollow.

In preferred embodiments, the wear-resistant particles form 50-70% by weight of the wear-resistant layer.

According to a further aspect of the present invention, there is provided a foil blade for use in processing sheet material comprising a polymer material in which is suspended wear-resistant particles.

Certain preferred embodiments of the invention will now be described with reference to the accompanying drawings; of which:-

- 3 -

Figure 1 shows a blade in accordance with a first embodiment 5 of the present invention;

Figure 2 shows a blade in accordance with a second embodiment of the present invention;

10

Figure 3 show a cross-sectional view of the blade shown in Figures 1 or 2; and

Figure 4 shows an alternative blade.

15

As shown in Figure 1, a blade 1 for use with paper mill equipment includes a substrate 3, preferably formed of plastics or a glass fibre composite material, and an adhesive mixture wear-resistant layer 2.

20

25

The wear-resistant layer may be formed using any suitable materials, although one or more of silicon carbide, tungsten, alumina, zirconia or chrome oxide are preferred for use as wear-resistant particles. Such particles are preferably provided within an epoxy material, e.g. a thermo setting or thermo plastics material. The particles are generally in the range of 50-70% by weight of the wear-resistant layer. With silicon carbide particles for example, the particles are preferably around 55% by weight of the wear-resistant layer.

30

The wear-resistant layer 2 may be applied to the substrate 3 using spraying techniques or may be applied mechanically, for example by extrusion techniques.

35 Additional blade surface materials may be applied to the adhesive layer whilst it is still sticky, i.e. whilst it has

WO 97/30212 PCT/GB97/00425

- 4 -

not dried. Such additional materials may be applied mechanically (cold) or by thermal spraying.

As shown in Figure 2, the wear-resistant layer may be formed by applying a layer of pre-made tiles 4 onto an adhesive layer 5 and filling the gaps 6 between the tiles with the epoxy adhesive composite mixture. Blades of over 10 metres can be produced in this way.

The pre-made tiles can be formed in any suitable manner, using for example casting or extrusion techniques. The tiles may be relatively short so that a number are required along the length of the blade, or relatively long so as to extend along the whole length of the blade.

15

The adhesive wear-resistant layer 2 may be applied to one or more of the faces of the blade substrate to provide a suitable wear-resistant layer. As shown in Figure 3, the substrate 3 may be recessed to assist in the application of the adhesive material. The recess will also result in a secure mounting of 20 the wear-resistant layer. The substrate may include a removable member 7 onto which the wear-resistant layer is For enhanced weight characteristics, the removable member 7 may be formed hollow, as shown by phantom-lines 9, The removable member 7 can facilitate as an extrusion. 25 reconditioning of the foil blade on wearing down of the layer The removable member can be dovetailed with the main substrate 3 for strength.

30 The substrate 3 may itself include a channel 8 for easy mounting thereof on a sub-structure.

10

Figure 4 shows an alternative blade structure where the blade is an integral member with no separate substrate. The blade comprises a polymer base material, such as a plastics material, in which is suspended wear-resistant particles of the sort described above. The blade may be cast or extruded.

It will be understood that the embodiments illustrated show an application of the invention in one form only for the purposes of illustration. In practice, the invention may be applied to many different configurations, the detailed embodiments being straightforward for those skilled in the art to implement.


CLAIMS

- 1. A method of manufacture of a blade comprising a substrate and a wear-resistant layer, the method including the step of:applying the wear-resistant layer in the form of an adhesive, the adhesive comprising wear-resistant particles suspended in an unset settable material.
- A method as claimed in claim 1, wherein the adhesive is
 sprayed onto the blade substrate.
 - 3. A method as claimed in claim 1, wherein the adhesive is extruded onto the blade substrate.
 - 15 4. A method as claimed in any preceding claim, wherein additional blade surface materials are applied whilst the adhesive is unset.
 - 5. A method as claimed in any preceding claim, further comprising the step of applying pre-formed wear-resistant tiles onto the blade substrace and applying the adhesive between edges of adjacent tiles.
 - 6. A blade manufactured according to the method of any preceding claim.
 - 7. A blade as claimed in claim 6, wherein the adhesive comprises a polymer in which is suspended any of silicon carbide, tungsten, alumina, zirconia or chrome oxide particles.
 - 8. A blade as claimed in claim 6 or 7, wherein the blade substrate is recessed to accept the adhesive.
 - 35 9. A blade as claimed in any one of claims 6 to 8, wherein the substrate comprises a removable member onto which the wear-resistant layer is formed.


30

- 7 -

- 10. A blade as claimed in any one of claims 6 to 9, wherein the wear-resistant particles are 50-70% by weight of the wear-resistant layer.
- 5 11. A foil blade for use in processing material in sheet form comprising a polymer material in which is suspended wear-resistant particles.
- 12. A blade substantially as hereinbefore described with 10 reference to Figures 1 to 3 or 4 of the accompanying drawings.
 - 13. A method substantially as hereinbefore described with reference to Figures 1 to 3 or 4 of the accompanying drawings.



SUBSTITUTE SHEET (RULE 26)



INTERNATIONAL SEARCH REPORT

Intr ional Application No PCT/GB 97/00425

A. CLASSI	FICATION OF SUBJECT MATTER D21F1/48 D21F1/38				
IPC 0	D2171740 D2171733		-		
According to International Patent Classification (IPC) or to both national classification and IPC					
B. FIELDS	SEARCHED				
Minimum d IPC 6	locumentation searched (classification system followed by class D21F B29C	ification symbols)			
Documenta	tion searched other than minimum documentation to the extent	that such documents are included in the fields i	cearched		
		and some week			
Electronic	data base consulted during the international search (name of dat	la base and, where practical, scal di como coco,	·		
C. DOCUI	MENTS CONSIDERED TO BE RELEVANT				
Category *	Citation of document, with indication, where appropriate, of	the relevant passages	Relevant to claim No.		
·X	FR 2 179 973 A (UNION CARBIDE November 1973	CORP) 23	1,3,4,6, 7,10-13		
Y	see the whole document		2,5,8,9		
X	PATENT ABSTRACTS OF JAPAN vol. 006, no. 197 (C-128), 6 October 1982 & JP 57 108139 A (HITACHI CHEM CO LTD), 6 July 1982, see abstract		1		
Y	US 5 387 172 A (HABENICHT HINF 7 February 1995 see column 2, line 25 - column figure 1		2		
		-/			
X Fu	rther documents are listed in the continuation of box C.	Patent family members are listed	l in annex.		
* Special categories of cited documents: The later document published after the international filing date or priority date and not in conflict with the application but					
"A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date		"X" document of particular relevance; the claimed invention carmot be considered novel or cannot be considered to involve an inventive step when the document is taken alone			
which citat 'O' docu	ment which may throw doubts on priority claim(s) or th is cited to establish the publication date of another ion or other specal reason (as specified) ment referring to an oral disclosure, use, exhibition or	"Y" document of particular relevance; the cannot be considered to involve an document is combined with one or	e claimed invention inventive step when the more other such docu-		
other means "P" document published prior to the international filing date but later than the priority date claimed		in the art.	ments, such combination being obvious to a person skilled in the art. '&' document member of the same patent family		
Date of th	ne actual completion of the international search	Date of mailing of the international	search report		
15 May 1997		04.06.	97		
Name and	d mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2	Authorized officer			
NL · 2280 HV Ripwijk Td. (+ 31-70) 340-2040, Tk. 31 651 epo nl, Far (+ 31-70) 340-3016		Guisan, T			

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Int ional Application No PCT/GB 97/00425

		PC1/GB 9/	700423
C.(Continu	dom) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages		Relevant to claim No.
Y	US 4 334 958 A (BALUHA GERALD F ET AL) 15 June 1982 see the whole document	•	5,8,9
Y	GB 1 103 261 A (FELDMÜHLE AKTIENGESELLSCHAFT) 14 February 1968 see page 2, column 1, line 17 - page 2, column 1, line 37 see page 3, column 1, line 13 - page 3, column 1, line 20; figures 1,3		5,8
A	FR 2 619 131 A (LOUSTAU PHILIPPE) 10 February 1989 see the whole document		3,11
A	GB 2 079 803 A (IRAPA VYVOJOVY A RACIONAL) 27 January 1982 see claim 1		11
٠			
	·		
	·		
		•	

1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int ional Application No PCT/GB 97/00425

	Patent document cited in search report	Publication date	Patent family member(s)	Publication date
	FR 2179973 A	23-11-73	AR 202624 A AT 334191 B AU 5436373 A BE 798094 A CA 1000684 A CH 575047 A DE 2318108 A GB 1420010 A JP 49014702 A NL 7305077 A SE 387385 B US 3975568 A	30-06-75 10-01-76 17-10-74 11-10-73 30-11-76 30-04-76 18-10-73 07-01-76 08-02-74 16-10-73 06-09-76 17-08-76
	US 5387172 A	07-02-95	DE 4226789 A EP 0582950 A FI 933592 A JP 6206657 A	17-02-94 16-02-94 14-02-94 26-07-94
	US 4334958 A	15-06-82	NONE	
	GB 1103261 A		NONE	
	FR 2619131 A	10-02-89	NONE	
	GB 2079803 A	27-01-82	NONE	
- 1				

Form PCT/ISA/210 (patent family annex) (July 1992)

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

□ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.